

TECHNICAL DATA SHEET

Ecomaxx Vinyl Floor Paint

Version: vJanuary2025

Product Description

Ecomaxx Vinyl Floor Paint is a premium water-based vinyl paint specially formulated to provide excellent, durable and washable finish on asbestos roofing tile, cement floor, brickwork, hard and softboards.

Recommended Use

Use on asbestos roofing tile, cement floor, brickwork, hard and softboards.

Application Methods

Applied By : Brush / Roller / Spray
Thinner : Clean Water
Clean Up : Clean Water

Technical Properties

Binder : Vinyl Acetate-Acrylic
Solids (% by Volume) : Approximately 35%
Specific Gravity : Approximately 1.10 to 1.20
Flash Point : Non-Flammable
Colour : Refer to Graphenstone Far East's Ecomaxx Colour Card for standard colours.
Finish : Low Sheen

Packaging & Storage

Packaging : 5L
Shelf Life : 12 months - Unopened
Storage : Cool, dry and well-ventilated area away from heat and direct sun light. Lid must be kept tightly closed.

Application Information

Substrate : Asbestos roofing tile, cement floor, brickwork, hard and softboards.

Recommended No. of Coats: 2

Recommended Dry Film Thickness:
30 to 40 µm / Coat

Theoretical Coverage: 9 to 10 m² / L / Coat
(Does not include substrate condition and loss factors)

Drying Time : Touch Dry 30 minutes
Recoat After 2 hours

Surface Preparation

For all substrate

Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.

Typical Recommended Painting System

For All Substrates

System	Product	No. of Coats
Primer	Ecomaxx Solvent Exterior Primer	1
Finish	Ecomaxx Vinyl Floor Paint	2

TECHNICAL DATA SHEET

Application & Cleaning Instructions

Paint is ready for use after thorough stirring. Thinning is not normally necessary, however, if required for better workability, do not exceed 5% of dilution ratio. Clean up equipment immediately after use.

Health & Safety

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. During spray application, do not breathe in mist and wear suitable respiratory protective equipment. Keep out of reach of children.

Complementary Products

It is recommended to use the Graphenstone and Ecomaxx products for complementary actions, according to the required application, repair and/or finish. Please, refer to the relevant Technical Data Sheets.

Usage Warnings

None in particular for normal use and people who do not have special pathologies. Alkaline product: protect skin and eyes especially. Apply with good ventilation, do not inhale product. Keep out of reach of children.

Waste Management

Help protect the environment, do not throw waste through the drain and use the nearest recycling centre.

Responsible Gesture

Minimize the product waste by estimating the amount you will need. Recover the unused paint to give it a new use, keep it under the above stated storage conditions.

Safety Information

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

Disclaimer

The above information is given to the best of our knowledge based on laboratory testing and practical experiences. The information in this data sheet may be subject to changes from time to time and without notice due to production refinements arising from continuing research and evaluation programmes, which may occasionally result in marginal changes in the coating properties.