

TECHNICAL DATA SHEET

Protective Coatings Road Marking Paint

Version: v01 January 2025

Product Description

Protective Coatings Road Marking Paint is a quick drying synthetic paint with exceptional durability. It is specially designed to maximize abrasion and chemical resistance.

Recommended Use

Use for the marking of road, car park, factories, schools, etc

Storage : Cool, dry and well-ventilated area away from heat and direct sun light. Lid must be kept tightly closed.

Technical Properties

Binder	: Alkyd
Solids (% by Volume)	: Approximately 50 to 60%
Flash Point	: About 23° C
Colour	: Refer to Graphenstone Far East's Ecomaxx Colour Card for standard colours.
Finish	: Reflective & Non-Reflective

Application Methods

Applied By	: Brush / Roller / Spray
Thinner	: General Thinner
Clean Up	: General Thinner

Surface Preparation

For All Surfaces

Surfaces must be dry, clean, sound and free from any loose material, dirt, grease or wax.

Typical Recommended Painting System

Substrate: Road

System	Product	No. of Coats
Primer	Not Required	-
Finish	Ecomaxx PC Road Marking Paint	2

Substrate: Concrete

System	Product	No. of Coats
Primer	Ecomaxx PC Solvent Exterior Primer	1
Finish	Ecomaxx PC Road Marking Paint	2

Application Information

Substrate: Road & Concrete

Recommended No. of Coats: 2

Recommended Dry Film Thickness:
30 to 40 µm / Coat

Theoretical Coverage: 9 to 10 m² / L /Coat
(Does not include substrate condition and loss factors)

Drying Time	: Touch Dry	20 Minutes
	: Hard Dry	1 hour
	: Recoat	After 1 hour

Packaging & Storage

Packaging : 5L

Shelf Life : 12 months - Unopened

TECHNICAL DATA SHEET

Application & Cleaning Instructions

Paint is ready for use after thorough stirring. Thinning is not normally necessary, however, if required for better workability, do not exceed 5% of dilution ratio. Clean up equipment immediately after use.

Health & Safety

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. During spray application, do not breathe in mist and wear suitable respiratory protective equipment. Keep out of reach of children.

Complementary Products

It is recommended to use the Graphenstone and Ecomaxx products for complementary actions, according to the required application, repair and/or finish. Please, refer to the relevant Technical Data Sheets.

Usage Warnings

None in particular for normal use and people who do not have special pathologies. Protect skin and eyes. Apply with good ventilation, do not inhale product. Keep out of reach of children.

Waste Management

Help protect the environment, do not throw waste through the drain and use the nearest recycling centre.

Responsible Gesture

Minimize the product waste by estimating the amount you will need. Recover the unused paint to give it a new use, keep it under the above stated storage conditions.

Safety Information

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

Disclaimer

The above information is given to the best of our knowledge based on laboratory testing and practical experiences. The information in this data sheet may be subject to changes from time to time and without notice due to production refinements arising from continuing research and evaluation programmes, which may occasionally result in marginal changes in the coating properties.