

TECHNICAL DATA SHEET

Protective Coatings Solvent Exterior Primer

Version: v01 January 2025

Product Description

Protective Coatings Solvent Exterior Primer is a premium solvent-based sealer for interior and exterior use.

Recommended Use

For use on both new and previously painted surfaces, such as masonry surface, brickwork, plaster, cement and asbestos.

Technical Properties

Binder	: Solvent-Based Acrylic
Specific Gravity	: Approximately 1.27
Flash Point	: About 23° C
Colour	: White
Finish	: Matt

Application Information

Substrate: Masonary & Asbestos

Recommended No. of Coats: 1

Recommended Dry Film Thickness:
30 to 40 µm / Coat

Theoretical Coverage: 10 - 12 m² / L / Coat
(Does not include substrate condition and loss factors)

Drying Time	: Touch Dry	30 minutes
	: Hard Dry	1 hour
	: Recoat	After 1 hour

Application Methods

Applied By : Brush / Roller / Spray

Thinner : General Thinner

Clean Up : General Thinner

Packaging & Storage

Packaging : 5L & 18L

Shelf Life : 12 months - Unopened

Storage : Cool, dry and well-ventilated area away from heat and direct sun light. Lid must be kept tightly closed.

Surface Preparation

For All Surfaces

Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease etc

Typical Recommended Painting System

For All Surfaces

<u>System</u>	<u>Product</u>	<u>No. of Coats</u>
Primer	Ecomaxx PC Solvent Exterior Primer 1	1
Finish	Graphenstone & Ecomaxx Ranges of Masonry Paints (Depending on application)	2

TECHNICAL DATA SHEET

Application & Cleaning Instructions

Paint is ready for use after thorough stirring. Thinning is not normally necessary, however, if required for better workability, do not exceed 5% of dilution ratio. Clean up equipment immediately after use.

Health & Safety

Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. During spray application, do not breathe in mist and wear suitable respiratory protective equipment. Keep out of reach of children.

Complementary Products

It is recommended to use the Graphenstone and Ecomaxx products for complementary actions, according to the required application, repair and/or finish. Please, refer to the relevant Technical Data Sheets.

Usage Warnings

None in particular for normal use and people who do not have special pathologies. Protect skin and eyes. Apply with good ventilation, do not inhale product. Keep out of reach of children.

Waste Management

Help protect the environment, do not throw waste through the drain and use the nearest recycling centre.

Responsible Gesture

Minimize the product waste by estimating the amount you will need. Recover the unused paint to give it a new use, keep it under the above stated storage conditions.

Safety Information

For information regarding safety, physical, ecological and toxicological information see the latest version of the product's Material Safety Data Sheet.

Disclaimer

The above information is given to the best of our knowledge based on laboratory testing and practical experiences. The information in this data sheet may be subject to changes from time to time and without notice due to production refinements arising from continuing research and evaluation programmes, which may occasionally result in marginal changes in the coating properties.